

GEYER SMART SOLUTIONS

Smart Wi-Fi Shutter Control Module

GS-SHUTTER · 1.7 A · 18.5 mm

Local wall control and remote operation of roller shutters, blinds, awnings and curtains through GEYER Smart.



POSITION 0–100% · Wi-Fi 2.4 GHz



REMOTE CONTROL

Open, stop, close and select the position through the GEYER Smart app.



POSITION CALIBRATION

Set the travel time for accurate position display and control from 0–100%.



LOCAL CONTROL

Operation through a compatible rocker switch or momentary push-buttons.



SCHEDULES & AUTOMATIONS

Weekly schedules and automations based on sunrise and sunset.

KEY TECHNICAL DATA

Input voltage	100–240 VAC
Frequency	50–60 Hz
Maximum current	1.7 A · inductive load
Position control	0–100% after calibration
Ingress protection	IP22
Wi-Fi	2.4 GHz
Dimensions	39 × 39 × 18.5 mm
Warranty	2 years

CONNECTED ECOSYSTEM



GEYER Smart

Control · Schedules · Automations

COMPATIBILITY



Amazon Alexa



Google Home



Tuya Smart



Smart Life

APP AVAILABLE ON



Smart shading for every space.

Precise control of shutters, blinds, awnings and curtains, locally and from your phone.



LIVING ROOM

Adjust shutters to manage daylight, privacy and comfort.



TERRACE / BALCONY

Operate a motorised awning remotely and create schedules.



BEDROOM

Schedule blinds or shutters to open and close automatically.



SHOP / HOSPITALITY

Automate shading according to opening hours and sunrise or sunset.

FROM INSTALLATION TO SMART CONTROL

1

INSTALLATION

Behind the wall switch

2

WIRING

Motor - S1 / S2

3

CALIBRATION

Position 0–100%

4

CONTROL

Locally and from your phone

IMPORTANT APPLICATION REQUIREMENTS

- Installation by a licensed electrician.
- Neutral conductor and 2.4 GHz Wi-Fi are required.
- Use a compatible motor up to 1.7 A.
- Calibration is required for 0–100% position control.



GEYER Smart

Shading control in one view

Open, stop, close, position control
and sunrise/sunset automations.