

1

GS-V02 - Smart Wi-Fi Water Valve

Variant selection and installation



REMOTE WATER SUPPLY CONTROL THREE VALVE VARIANTS

0-100% opening adjustment, schedules and automations through Geyer Smart.

Power supply	DC 5 V / 2 A
Maximum pressure	1.0 MPa (10 bar)
Protection	IP65
Network	Wi-Fi 2.4 GHz

VARIANT SELECTION

GS-V02-DN15

DN15 · 1/2" BSP

GS-V02-DN20

DN20 · 3/4" BSP

GS-V02-DN25

DN25 · 1" BSP

INSTALLATION STEPS

- 1 Select the correct code and confirm the BSP connection.
- 2 Isolate the water supply and check the flow direction.
- 3 Fit the valve using sealed, compatible connections.
- 4 Connect the supplied DC 5 V / 2 A adapter in a protected location.

PRODUCT OVERVIEW



MANUAL BUTTON

Short press: open / close

Hold for 5 s: pairing mode

Blue LED: Wi-Fi status

BEFORE PAIRING

2.4 GHz Wi-Fi · Internet · Bluetooth enabled.

Keep the phone close to the valve.

SAFE INSTALLATION



Qualified installer and isolated water supply.

IP65 PROTECTION



Do not immerse. Protect the adapter and connections.

2

Pairing and basic use

GEYER Smart | Wi-Fi 2.4 GHz



GEYER Smart

Download the app and create an account or sign in to your existing account.



SCAN TO DOWNLOAD

Select "Sign Up" or sign in.

ADD & PAIR IN 5 STEPS

The phone must be connected to 2.4 GHz Wi-Fi with Internet access.

1

Tap "+" or "Add Device".

2

Hold the button for 5 s until the blue LED flashes rapidly.

3

Tap "Add" and enter the Wi-Fi network and password.

4

Wait and tap "Done".

5

Check opening, position percentage and schedules.

BASIC FUNCTIONS



OPEN / CLOSE

Remote and local control.



POSITION 0-100%

Opening adjustment in 10% steps.



SCHEDULES

Up to 30 schedules per day.



AUTOMATIONS

Works with a leak sensor.

IF PAIRING FAILS

Check 2.4 GHz Wi-Fi, Internet, Bluetooth and the network password.

Move the phone and valve closer to the router.

Hold the manual button again for 5 s until the blue LED flashes rapidly.



MANUALS & DOCUMENTS

Scan for the detailed manual and all other product documents.